



**Manual drive stacker
model HV 1008**

**Manual drive stacker
model HV 1016**

Capacity 1000 kg

Ideal for the occasional, internal application of stacking and transporting of palletised goods.

Features

- Ergonomic safety control handle for one-hand operation of lifting, driving and lowering.
- Easy handling due to forced steering rollers.
- Lowering speed can be finely metered for sensitive lowering of the load.
- Single-acting hand pump with increased lift per handle stroke.
- Quick-lift for loads up to 100 kg.
- Robust mast construction with hard chromium plated piston.
- Steering roller with brake for safe parking of the hand stacker.



Technical data model HV 1008 and model HV 1016

Model	HV 1008	HV 1016
Art.-No.	034518032	034518030
Capacity, kg	1000	1000
Load center c, mm	600	600
Wheelbase y, mm	1075	1075
Weight, kg	179	205
Tyre type ¹	PUR/PUR	PUR/PUR
Steering rollers, mm	180x50	180x50
Load rollers, mm	80x55	80x55
Number of wheels/load rollers	2/2	2/2
Height, mast retracted h1, mm	1300	1965
Free lift h2, mm	810	1510
Stroke h3, mm	810	1510
Height, mast extended h4, mm	1300	1965
Lifting height max. h3 + h13, mm	900	1600
Fork height lowered h13, mm	90	90
Overall length L1, mm	1675	1675
Length incl. apron L2, mm	552	552
Overall width B, mm	765	765
Fork height s, mm	60	60
Fork width e, mm	60	60
Fork length l, mm	1122	1122
Outside dimension of forks b1, mm	570	570
Ground clearance m1, mm	25	25
Aisle width pallet Ast, mm	1875	1875
Turning circle radius Wa, mm	1445	1445
Lift per one crank rotation with/without load, mm	17/50	17/50

¹ PUR... Polyurethane

